

# GMK 4100L

CAPACIDADE MÁXIMA: 100t

COMPRIMENTO LANÇA: 11.65 / 60.0m

COMPRIMENTO JIB: 10.0 / 22.0m



PATOLAS INTEIRAMENTE EXTENDIDAS

PATOLAS FRONTAL: EXTENDIDA (360°) NÃO EXTENDIDA (LATERAIS E TRASEIRA)

A \ B	11.65*m	11.65m	15.90m	20.11m	24.26m	28.25m	32.11m	35.83m	40.08m	44.29m	48.43m	52.43m	56.28m	60.00m
2.5m	100.0													
3.0m	69.0	69.5	63.5	59.0	56.0									
4.0m	59.0	58.5	56.0	52.5	49.5	47.0								
5.0m	52.0	50.0	49.5	47.0	44.5	41.5	37.5	30.0						
6.0m	46.0	43.5	44.0	41.5	40.5	38.0	36.5	30.0	23.0					
7.0m	41.0	38.0	38.5	37.5	36.5	35.0	33.5	30.0	23.0	18.0				
8.0m	36.0	34.0	34.5	34.0	33.0	32.0	31.0	29.5	23.0	18.0	14.3			
9.0m	30.0	30.0	31.0	31.0	30.0	29.5	28.5	28.0	22.5	18.0	14.3	11.6		
10.0m			28.0	28.5	27.5	27.5	26.0	26.0	21.5	18.0	14.3	11.6	9.5	
11.0m			25.5	25.5	25.5	25.5	24.0	24.0	20.5	17.7	14.3	11.6	9.5	8.0
12.0m			22.5	23.0	22.5	23.0	21.5	21.5	19.1	17.0	14.3	11.6	9.5	8.0
13.0m			19.7	20.0	19.8	20.5	19.7	19.3	17.9	16.2	14.2	11.6	9.5	8.0
14.0m				17.7	18.3	18.1	18.6	17.5	16.4	15.3	14.0	11.6	9.5	8.0
15.0m				16.4	16.5	16.2	16.8	15.9	14.9	14.4	13.3	11.5	9.5	8.0
16.0m				14.8	14.8	14.8	15.2	14.6	13.6	13.1	12.6	11.3	9.5	8.0
18.0m					12.2	12.8	12.5	12.0	12.4	11.0	10.8	10.6	9.5	8.0
20.0m					10.8	10.8	10.5	10.4	10.5	9.3	9.2	9.2	9.0	8.0
22.0m						9.2	8.9	9.4	8.9	7.9	7.8	7.9	8.0	7.7
24.0m						8.0	8.2	8.1	7.6	6.6	7.1	6.9	7.1	7.1
26.0m							7.4	7.0	6.5	6.0	6.6	6.3	6.4	6.2
28.0m							6.5	6.1	5.6	5.3	6.0	5.6	5.7	5.4
30.0m								5.4	4.9	5.0	5.3	5.2	5.1	4.7
32.0m								4.7	4.2	4.6	4.6	4.6	4.4	4.1
34.0m									3.9	4.4	4.1	4.1	3.9	3.5
36.0m									3.2	4.0	3.8	3.6	3.4	3.0
38.0m										3.5	3.4	3.2	2.9	2.6
40.0m										3.1	3.0	2.8	2.5	2.2
42.0m											2.7	2.4	2.2	1.8
44.0m											2.4	2.1	1.8	1.5
46.0m												1.8	1.5	1.2
48.0m												1.6	1.3	0.9
50.0m													1.0	

A: ALTURA DA LANÇA

B: RAIOS DE OPERAÇÃO