

SANNY 600

CAPACIDADE MÁXIMA: 600t

COMPRIMENTO LANÇA: 16.4 / 95.0m

COMPRIMENTO JIB: 18.0 / 84.0m

PATOLAS INTEIRAMENTE EXTENDIDAS

PATOLAS FRONTAL: EXTENDIDA (360°) NÃO EXTENDIDA (LATERAIS E TRASEIRA)



B	A	16.4 _m	21.6 _m	26.8 _m	32.0 _m	37.1 _m	42.3 _m	47.5 _m	52.6 _m	57.8 _m	62.9 _m	
2.5 _m		600.0										
3.0 _m		225.0										
3.5 _m		225.0	225.0									
4.0 _m		225.0	225.0									
4.5 _m		220.0	225.0	172.0								
5.0 _m		215.0	215.0	167.0	185.3							
6.0 _m		210.0	206.0	160.0	181.0	175.0						
7.0 _m		198.0	195.0	151.0	178.0	173.0	165.0					
8.0 _m		180.0	178.0	141.5	165.0	157.0	160.0	155.0				
9.0 _m		166.5	162.6	132.0	155.0	150.0	143.0	147.0	87.5	105.0		
10.0 _m		153.0	153.0	125.0	150.0	140.0	135.0	128.0	83.0	96.0	82.0	
12.0 _m		125.0	127.5	110.0	125.0	125.0	122.0	115.0	77.3	85.0	78.0	
14.0 _m			110.0	98.0	106.0	108.0	106.0	100.0	74.1	73.1	68.0	
16.0 _m			88.0	90.0	93.0	95.5	88.5	86.1	70.3	63.8	60.6	
18.0 _m			71.0	81.7	82.3	83.0	76.6	76.6	67.6	56.9	51.5	
20.0 _m				72.5	73.4	74.5	67.8	68.7	63.5	53.3	46.5	
22.0 _m				65.0	65.3	66.0	60.5	61.2	60.6	49.4	44.8	
24.0 _m					56.3	58.0	53.0	58.0	55.9	45.3	42.4	
26.0 _m					49.2	51.3	47.5	52.7	51.8	41.6	39.1	
28.0 _m					39.4	46.3	43.0	47.9	47.9	38.4	36.2	
30.0 _m						41.8	39.0	43.5	43.1	35.0	33.7	
32.0 _m						36.2	35.0	38.2	38.7	32.5	30.3	
34.0 _m						22.5	31.1	35.3	34.8	30.4	27.7	
36.0 _m							27.8	33.3	32.4	28.3	25.9	
38.0 _m								23.9	29.5	31.2	26.5	24.3
40.0 _m								12.2	26.0	28.5	25.0	22.4
42.0 _m									23.5	25.8	23.0	21.0
44.0 _m									16.7	23.5	21.5	19.2
46.0 _m										21.6	18.2	17.3
48.0 _m										18.0	16.8	15.5
50.0 _m										10.0	15.1	14.4
52.0 _m											13.5	12.9
54.0 _m												11.5
56.0 _m												10.1
58.0 _m												8.9
60.0 _m												4.0

A: ALTURA DA LANÇA

B: RAIOS DE OPERAÇÃO