

SANY 400

CAPACIDADE MÁXIMA: 400t

COMPRIMENTO LANÇA: 15,7 / 90,0m

COMPRIMENTO JIB: 18,0 / 78,0m



PATOLAS INTEIRAMENTE EXTENDIDAS

PATOLAS FRONTAL: EXTENDIDA (360°) NÃO EXTENDIDA (LATERAIS E TRASEIRA)

A	B	15.7m	20.6m	25.5m	30.4m	35.3m	40.2m	45.1m	50.0m	54.9m	59.8m	64.7m	69.6m	74.5m	79.4m	84.1m	90m
2.6m	400.0*																
3.0m	350.0 *																
3.5m	230.0 *	175.0															
4.0m	208.0 *	175.0	170.0														
4.5m	190.0	175.0	166.0	150.0													
5m	175.0	165.0	163.0	148.0	130.0												
6.0m	160.0	155.0	153.0	142.0	128.0	110.0											
7.0m	145.0	140.0	138.0	133.0	125.0	108.0	95.0										
8.0m	130.0	126.2	126.0	123.0	120.0	105.0	93.0	80.0									
9.0m	120.0	116.9	117.1	113.0	110.0	103.0	90.0	77.0	67.0								
10.0m	110.0	108.0	107.0	107.5	100.0	95.0	87.0	73.0	63.0	53.0							
11.0m	95.0	95.0	95.0	95.0	93.0	87.0	82.0	67.0	61.0	51.0	46.0						
12.0m	85.0	90.0	90.0	90.0	85.0	80.0	76.0	64.0	59.0	50.3	44.0	36.0					
13.0m	75.0	84.0	83.0	80.0	78.0	73.0	71.2	61.0	55.0	48.0	43.0	35.0	29.0				
14.0m		78.0	76.0	75.0	73.0	68.0	66.7	58.0	53.0	46.0	41.0	33.3	28.0	23.0			
16.0m		65.0	65.0	63.0	63.0	61.0	58.4	52.5	48.5	41.0	37.0	30.7	27.0	22.5	17.0	12.5	
18.0m		50.0	56.5	55.0	56.0	53.2	52.0	48.5	44.6	37.0	34.0	28.3	26.0	21.5	16.9	12.5	
20.0m			49.0	49.0	50.0	47.4	46.3	44.5	40.5	34.4	31.0	26.6	25.0	20.5	16.5	12.5	
22.0m			40.0	43.3	44.3	43.0	42.0	41.0	36.7	31.7	27.8	24.8	23.5	19.5	16.3	12.5	
24.0m				37.7	38.6	38.9	38.1	36.0	33.8	28.8	25.6	22.7	22.0	18.5	16.0	12.3	
26.0m				33.1	34.0	35.1	34.5	32.0	30.7	26.5	23.6	20.9	20.3	17.5	15.4	12.1	
28.0m					30.1	31.2	31.8	30.1	28.3	24.5	21.8	19.7	18.5	16.5	14.5	11.9	
30.0m					26.8	29.2	28.8	28.2	26.1	22.5	20.1	18.6	17.5	15.7	13.6	11.6	
32.0m					24.0	26.9	26.1	26.4	24.0	20.8	18.5	16.7	16.2	14.6	13.0	11.0	
34.0m						25.2	23.6	24.3	22.5	19.1	17.3	15.6	15.2	13.9	12.5	10.5	
36.0m						23.6	21.4	22.5	20.7	18.0	16.0	14.5	14.3	13.1	12.0	9.9	
38.0m							19.5	20.6	19.4	16.6	15.0	13.5	13.4	12.5	11.5	9.4	
40.0m							17.8	18.8	17.8	15.2	13.8	12.7	12.3	11.7	11.0	9.0	
42.0m								17.3	16.2	14.3	13.0	11.8	11.5	11.1	10.5	8.6	
44.0m									15.9	14.7	13.1	11.9	11.0	10.7	10.5	9.9	8.2
46.0m									14.5	13.4	12.4	11.0	10.5	10.2	9.8	9.4	7.8
48.0m										12.2	11.6	10.3	9.3	9.5	9.1	8.8	7.4
50.0m											11.1	10.7	9.4	8.6	8.8	8.5	7.1
52.0m												9.8	8.8	8.0	8.3	7.9	6.8
54.0m													8.8	8.2	7.6	7.5	6.5
56.0m														8.0	7.6	7.0	6.0
58.0m															6.9	6.8	5.5
60.0m																6.6	5.1
62.0m																	4.7
64.0m																	4.3
66.0m																	4.1
68.0m																	3.8
70.0m																	3.5
72.0m																	3.2
74.0m																	2.9
76.0m																	2.5
78.0m																	2.2
80.0m																	1.8

A: ALTURA DA LANÇA

B: RAIOS DE OPERAÇÃO