

# STC 1600

CAPACIDADE MÁXIMA: 160t

COMPRIMENTO LANÇA: 14.1 / 75.5m

COMPRIMENTO JIB: 9.0 / 27.0m

PATOLAS INTEIRAMENTE EXTENDIDAS

PATOLAS FRONTAL: \* EXTENDIDA (360°) NÃO EXTENDIDA (LATERAIS E TRASEIRA)



A B	14.1m	18.8m	23.5m	28.2 m	32.9m	37.6m	42.3m	47.0m	51.7m	56.4 m	61.1m	65.8m	70.5 m	75.5m
2.5m	160.0*													
3.0m	130.0*	115.0*												
3.5m	126.0*	110.0*	98.0											
4.0m	117.0*	106.0*	98.0											
4.5m	109.0	101.0	98.0											
5m	100.0	96.0	94.0	85.0*										
5.5m	93.0	90.0	87.5	81.5										
6.0m	86.0	85.0	81.0	78.0	72.0*									
6.5m	79.5	79.0	76.0	74.0	72.0*									
7.0m	75.0	73.0	71.5	70.0	72.0*	59.0								
7.5m	68.5	68.0	67.0	66.0	67.5	57.5								
8.0m	64.0	63.0	63.5	62.5	63.5	56.0	52.0							
9.0m	55.5	55.5	55.8	55.0	56.0	53.5	49.0	37.0						
10.0m	49.5	49.5	50.0	50.0	51.0	50.0	46.0	36.0	31.5					
12.0m		40.0	40.8	41.0	42.0	41.0	41.5	31.8	29.8	25.0				
14.0m		33.0	34.2	34.0	35.2	34.5	35.0	28.4	26.6	22.0	19.2	16.2		
16.0m			29.0	29.0	30.0	29.5	30.0	25.5	23.7	20.0	17.6	15.6	12.7	9.2
18.0m			25.2	25.0	26.0	26.0	26.0	22.0	21.2	18.5	16.3	15.2	12.6	9.2
20.0m				21.5	22.7	23.0	22.7	19.3	19.1	17.0	14.2	13.7	12.5	9.1
22.0m				19.0	20.0	20.5	20.0	17.1	17.3	15.3	13.1	12.5	11.5	9.0
24.0m					18.1	18.5	17.8	15.2	15.5	13.9	12.1	11.5	10.1	8.9
26.0m					16.4	16.5	15.9	13.6	13.9	12.7	11.3	10.5	9.5	8.4
28.0m						15.0	14.3	12.3	12.6	11.7	10.6	10.0	8.9	7.8
30.0m						13.5	12.8	11.2	11.5	10.8	10.0	9.2	8.4	7.3
32.0m							11.6	10.2	10.4	10.0	9.3	8.5	8.0	6.9
34.0m							10.4	9.3	9.6	9.3	8.7	8.0	7.5	6.6
36.0m								8.5	8.7	8.7	8.1	7.5	7.0	6.3
38.0m								7.7	7.9	7.8	7.5	7.1	6.6	6.0
40.0m									7.2	7.3	6.8	6.7	6.2	5.7
42.0m									6.6	6.6	6.3	6.1	5.9	5.4
44.0m										6.0	5.9	5.6	5.5	5.1
46.0m										5.5	5.6	5.2	5.1	4.8
48.0m											5.3	4.9	4.7	4.5
50.0m											5.0	4.7	4.3	4.2
52.0m												4.4	4.0	3.9
54.0m												4.2	3.7	3.5
56.0m													3.3	3.2
58.0m													3.0	2.8
60.0m														2.6
62.0m														2.3
64.0m														2.0