

# STC 1100T6

CAPACIDADE MÁXIMA: 100t

COMPRIMENTO LANÇA: 12.9 / 60.0m

COMPRIMENTO JIB: 10.0 / 17.5m



PATOLAS INTEIRAMENTE EXTENDIDAS

PATOLAS FRONTAL: EXTENDIDA (360°) NÃO EXTENDIDA (LATERAIS E TRASEIRA)

A B	12.9m	17.3m	21.6m	25.9m	30.3m	34.6m	38.9m	43.2m	47.5m	51.9m	56.1m	60.0m
2.5m	110.0*											
3.0m	90.0	80.0										
3.5m	86.0	80.0	72.0									
4.0m	79.5	77.0	72.0	68.0								
4.5m	74.0	71.8	69.0	65.0								
5m	69.0	67.0	65.3	64.0	60.0							
5.5m	64.5	62.5	61.5	60.0	57.5							
6.0m	60.5	59.0	58.2	56.5	55.0	47.5						
6.5m	55.2	54.8	54.3	53.5	52.5	46.0						
7.0m	50.0	51.1	50.5	50.1	50.2	44.0	36.5					
7.5m	46.6	47.8	47.3	47.0	47.2	42.5	34.5					
8.0m	43.6	45.0	44.5	44.5	45.0	40.5	34.0	30.0				
9.0m	37.0	40.0	40.0	39.1	40.0	37.0	33.0	27.3				
10.0m		35.5	35.8	35.0	35.2	34.0	30.0	25.0	26.0			
12.0m		29.0	29.0	28.5	29.0	30.0	25.4	21.3	22.5	21.0	16.6	
14.0m			24.0	23.7	24.3	24.5	21.6	18.4	19.7	18.8	15.5	13.5
16.0m			19.8	19.8	20.2	20.5	18.8	16.2	17.0	16.8	15.0	13.4
18.0m				16.5	17.5	17.0	16.4	14.3	14.9	14.8	14.3	12.9
20.0m				13.7	15.0	14.5	14.5	12.7	13.2	13.0	12.3	11.7
22.0m					13.0	12.4	12.4	11.3	11.7	11.6	10.8	10.6
24.0m					11.4	10.9	10.8	10.0	10.5	10.5	9.7	9.2
26.0m						9.6	9.5	9.2	9.5	9.0	8.8	8.3
28.0m						8.6	8.4	8.3	8.7	8.1	8.0	7.5
30.0m							7.5	7.6	7.6	7.4	7.0	6.9
32.0m							6.7	6.8	6.8	6.9	6.2	6.2
34.0m								6.1	6.1	6.1	5.5	5.3
36.0m								5.5	5.5	5.5	4.9	4.7
38.0m									5.0	4.9	4.3	4.2
40.0m									4.5	4.4	3.9	3.7
42.0m										3.9	3.4	3.3
44.0m										3.5	3.0	2.9
46.0m											2.7	2.6
48.0m											2.3	2.3
50.0m												2.0
52.0m												1.6

A: ALTURA DA LANÇA

B: RAIOS DE OPERAÇÃO