

STC 1600

CAPACIDADE MÁXIMA: 160t

COMPRIMENTO LANÇA: 14.1 / 75.5m

COMPRIMENTO JIB: 9.0 / 27.0m



B	A	14.1m	18.8m	23.5m	28.2m	32.9m	37.6m	42.3m	47.0m	51.7m	56.4m	61.1m	65.8m	70.5m	75.5m
2.5m	160.0*														
3.0m	130.0*	115.0*													
3.5m	126.0	110.0	98.0												
4.0m	117.0	106.0	98.0												
4.5m	109.0	101.0	98.0												
5.0m	100.0	96.0	94.0	85.0*											
5.5m	93.0	90.0	87.5	81.5											
6.0m	86.0	85.0	81.0	78.0	72.0*										
6.5m	79.5	79.0	76.0	74.0	72.0*										
7.0m	75.0	73.0	71.5	70.0	72.0*	59.0									
7.5m	68.5	68.0	67.0	66.0	67.5	57.5									
8.0m	64.0	63.0	63.5	62.5	63.5	56.0	52.0								
9.0m	55.5	55.5	55.8	55.0	56.0	53.5	49.0	37.0							
10.0m	49.5	49.5	50.0	50.0	51.0	50.0	46.0	36.0	31.5						
12.0m		40.0	40.0	40.8	41.0	42.0	41.0	41.5	31.8	29.8	25.0				
14.0m		33.0	34.2	34.0	35.2	34.5	35.0	28.4	26.6	22.0	19.2	16.2			
16.0m			29.0	29.0	30.0	29.5	30.0	25.5	23.7	20.0	17.6	15.6	12.7	9.2	
18.0m			25.2	25.0	26.0	26.0	26.0	22.0	21.2	18.5	16.3	15.2	12.6	9.2	
20.0m				21.5	22.7	23.0	22.7	19.3	19.1	17.0	14.2	13.7	12.5	9.1	
22.0m				19.0	20.0	20.5	20.0	17.1	17.3	15.3	13.1	12.5	11.5	9.0	
24.0m					18.1	18.5	17.8	15.2	15.5	13.9	12.1	11.5	10.1	8.9	
26.0m					16.4	16.5	15.9	13.6	13.9	12.7	11.3	10.5	9.5	8.4	
28.0m						15.0	14.3	12.3	12.6	11.7	10.6	10.0	8.9	7.8	
30.0m						13.5	12.8	11.2	11.5	10.8	10.0	9.2	8.4	7.3	
32.0m							11.6	10.2	10.4	10.0	9.3	8.5	8.0	6.9	
34.0m							10.4	9.3	9.6	9.3	8.7	8.0	7.5	6.6	
36.0m								8.5	8.7	8.7	8.1	7.5	7.0	6.3	
38.0m								7.7	7.9	7.8	7.5	7.1	6.6	6.0	
40.0m									7.2	7.3	6.8	6.7	6.2	5.7	
42.0m									6.6	6.6	6.3	6.1	5.9	5.4	
44.0m										6.0	5.9	5.6	5.5	5.1	
46.0m										5.5	5.6	5.2	5.1	4.8	
48.0m											5.3	4.9	4.7	4.5	
50.0m											5.0	4.7	4.3	4.2	
52.0m												4.4	4.0	3.9	
54.0m												4.2	3.7	3.5	
56.0m													3.3	3.2	
58.0m													3.0	2.8	
60.0m														2.6	
62.0m														2.3	
64.0m														2.0	

A: ALTURA DA LANÇA

B: RAIOS DE OPERAÇÃO

www.mongel.com.br